

The bright way to Light

## INTRODUCING

## Stylish and classic lighting for a variety of open spaces



Our new design LED Light Lily is a **revolutionary product**, developed for **space lighting and accent lighting** with a built-in driver, and designed with a **stylish, classic and clean look.** 





A perfect luminaire light for open space areas across many different applications for both residential and commercial interiors



EXAMPLE

Dimension: Ø15"x3.5" Power & Lumen Output: 26W: 2600lm @ 4000K 36W: 3600lm @ 4000K **Color Temperature** Warm White: 3000K ±200K Natural White: 4000K ± 250K Daylight White: 5000K ± 300K Pure White: 5700K ±350K Color Rendering Index: >80 Rated Life (L70): 50,000 hours Housing: Aluminum **Optics:** Opal/Micro Prismatic Beam Spread: Up/Down Operating Temperature: -20°C to +60°C (Amb.) Input Voltage: 200-240V/AC Power Factor: >0.95 Working Voltage: 26W: 26±2 V/DC 36W: 46±3 V/DC Working Current: 700 mA Net Weight: 2.5 Kg Glow Wire: 650°C (850°C Optional) IP: IP20 IK: IK05

Installation:

FEATURES

Pendant Mounted Ultra modern and stylish innovative design Excellent light distribution; a blend of space + accent lighting: innovative hybrid of edge-lit and back-lit lighting technology. Color variable, different color for spatial and accent lighting Energy efficient, > 100lm/W Anti-Glare UGR19 No UV or IR emissions Durable with life span over 35,000 hours Environmentally friendly - fully recyclable,

no mercury or other hazardous materials Simple and convenient installation

DIMMABLE

2.4 GHz

E476593



Part Number	Power	ССТ	Lumen Output	Beam	Dimension
SL-PAN-26W-WW-LY	26W		2600	Up/Down	
SL-PAN-26W-NW-LY	26W		2600	Up/Down	
SL-PAN-26W-DW-LY	26W	WW=3000 ±200K	2600	Up/Down	
SL-PAN-26W-PW-LY	26W	<b>NW</b> =4000 ±250K	2600	Up/Down	Ø15"X3.5"
SL-PAN-36W-WW-LY	36W	<b>DW</b> =5000 ±300K	3600	Up/Down	013 7.3.3
SL-PAN-36W-NW-LY	36W	<b>PW</b> =6000 ±350K	3600	Up/Down	
SL-PAN-36W-DW-LY	36W		3600	Up/Down	
SL-PAN-36W-PW-LY	36W		3600	Up/Down	

Non Flicker

PF > 0.95