

INTRODUCING

PANEL LIGHT

Low-Cost Panel light with superior performance capabilities with advanced energy savings and long life

The Light Master

Slim LED Panel Light

adopts qualified super

bright LED as a light

source, which is stable,

long life and no UV &

IR emission. The

anodized aluminum frame
is stylish and fashionable
with everlasting color.

The panel light is
energy efficient, uniform,
high lumen output is the
ideal replacement for
traditional gird lights and

fluorescent tubes.



The
Light Master
Panel light creates
an industry leading
conformity and consistency.
With various energy saving features, this
is the perfect panel light for all applications.



An amazing 125 Lm / Watt

Durable and rugged White Aluminum Frame

No sag or bend in this specially designed frame.

Non Flicker Driver Operation SMD 2835

No UV or IR emissions.

Warranty — 5 Years, 50,000 hours

Color Temperature Availability Pure White 4000 K

Cool White



| Part Number | Panel Size | Power | ССТ | Lumen Output | Beam | Dimensions |
|---------------------|---------------|-------|---------------|-----------------|-------|-----------------|
| LM-PNL-40W24-48DDML | 4' x 2' | 40 W | 4000K / 5000K | 5000 | 120 D | 47.75" x 23.74" |
| LM-PNL-50W24-48DDML | 4' x 2' | 50 W | 4000K / 5000K | 6250 | 120 D | 47.75" x 23.74" |
| LM-PNL-40W24-24DDML | 2' x 2' | 30 W | 4000K / 5000K | 3750 | 120 D | 23.74" x 23.74" |
| LM-PNL-50W24-24DDML | 2' x 2' | 35 W | 4000K / 5000K | 6250 | 120 D | 23.74" x 23.74" |
| LM-PNL-30W12-48DDML | 1' x 4' | 30 W | 4000K / 5000K | 3750 | 120 D | 47.75" x 11.92 |
| LM-PNL-35W12-48DDML | 1' x 4' | 35 W | 4000K / 5000K | 6250 | 120 D | 47.75" x 11.92 |















