




INTRODUCING
FLAT-LINEAR

The budget solution to
light your work space.

This **low cost economical Flat Linear light** is perfect for both your High Bay and Low Bay Lighting applications. With its slim design, the Flat Linear is the perfect LED replacement for T5 and T8 fluorescent high bays. The Flat Linear delivers **energy efficient, uniform, high lumen high-performance optics** which delivers clear or whiter, **brighter light while using significantly less energy** when compared to traditional high bay lighting.




A new generation of LED Highbay Lighting that complements and reinforces our LED Bay Light industrial lighting.

RESIDENTIAL GARAGES • WAREHOUSES • INDUSTRIAL AREAS • GYMNASIUMS
EXHIBITION HALLS • WORKSHOPS • MANUFACTURING FACILITIES • DISTRIBUTION CENTERS
STORAGE AREAS • GROCERY STORES • HIGH BAY AND LOW BAY GARAGES • BIG BOX RETAILERS

FEATURES

- Choose from two popular sizes:
 110W - 23.6"L x 13.6"W x 2.2"T
 220W - 47.2"L x 13.6"W x 2.2"T
- Choose from four different optional operating functions:
 DM - Dimming function
 SN - Sensing function
 SD - Sensing plus Dimming function
 EP - Emergency Function
- An amazing 130 Lumens per watt
- Changeable Beam Angle of 30, 60, 120 degree
- Easy installation chain mounting included
- Optional wire guard for protection
- Optional remote controller of microwave motion sensor
- Five year warranty

DIMENSIONS



Dimensions	
23.6"L x 13.6"W x 2.2"T	
47.2"L x 13.6"W x 2.2"T	

SPECIFICATIONS

- Non Flicker Driver Operation**
- Power and Lumen Output**
 110W - 14,300 Lumens
 220W - 28,600 Lumens
- Color Temperature Available**
 Warm White 3000K ± 5%
 Natural White 4000K ± 5%
 Pure White 5000K ± 5%
 Bright White 5700K ± 5%
- IP 65 Rated for performance**
- Color Rendering Index >80**
- Rated Lifetime 54,000 hours**
- Housing White Die Cast Aluminum**
- Operating Temperature**
 -20 °C to + 50 °C (Amb.)
- Input Voltage AC - 120 - 277 Volts**
 1 - 10 V dimmable feature

Item Number	Luminous Efficacy	Watt (W)	LED		Dimmable (inch)	Dimension (inch)	Input Voltage	Driver Brand
			LED Brand	LED type				
PHB06-110DM-CCL0	130LM/W	110W	Jufei	SMD2835	1-10v dimmable	L23.6*W13.6*H2.2	AC120-277V	Xiezhen
PHB06-160DM-CCL0		160W				L23.6*W13.6*H2.2		
PHB06-220DM-CCL0		220W				L47.2*W13.6*H2.2		
PHB12-220DM-CCL0		220W				L47.2*W13.6*H2.2		
PHB12-320DM-CCL0		320W				L47.2*W13.6*H2.2		